

MLID

REACH RS2+

Datasheet



Key features

- Tracks GPS/QZSS L1C/A, L2C; GLONASS L1OF, L2OF; BeiDou B1I, B2I; Galileo E1-B/C, E5b
- Fast RTK convergence
- Multi-feed antenna with multipath rejection
- 868/915 MHz LoRa modem for up to 8 km connectivity
- Global LTE modem
- 22 hours on 1 charge
- NTRIP and VRS support, works with RTCM3
- Logs RINEX at update rate up to 10 Hz
- 16 GB of internal storage
- IP67, water and dustproof

ATyges

REACH RS2+

Technical specifications

POSITIONING

Precision	Static	H: 4 mm+0.5 ppm V: 8mm+1 ppm
	PPK	H: 5 mm+0.5 ppm V: 10 mm+1 ppm
	RTK	H: 7 mm+1 ppm V: 14 mm+1 ppm
Convergence time	~5 s typically	
Signal tracked	GPS/QZSS L1C/A, L2C, GLONASS L1OF, L2OF, BeiDou B1I, B2I, Galileo E1-B/C, E5b	
Number of channels	184	
Update rates	Up to 10 Hz	
IMU	9DOF	

CONNECTIVITY

UHF LoRa radio	Frequency range	868/915 MHz
	Power	0.1W
	Distance	Up to 8 km
LTE modem	Regions	Global
	Bands	FDD-LTE: 1, 2, 3, 4, 5, 7, 8, 12, 13, 18, 19, 20, 26, 28, 66 TD-LTE: 38, 40, 41 UMTS (WCDMA/FDD): 1, 3, 2, 4, 5, 6, 8, 19 Quad-Band, 850/1900, 900/1800 MHz
	SIM card	Nano-SIM
Wi-Fi	802.11 b/g/n	
Bluetooth	4.0/2.1 EDR	
Ports	RS-232, USB Type-C	
Data Protocols	Corrections	NTRIP, RTCM3
	Position output	NMEA, LLH/XYZ
Data logging	RINEX at update rate up to 10 Hz	
Internal storage	16 GB	

MECHANICAL

Dimensions	126x126x142 mm
Weight	950 g
Temperature	-20...+65 °C
Ingress protection	IP67 water and dustproof

ELECTRICAL

Autonomy	16 hrs as LTE RTK rover,
Battery	LiFePO4 6400 mAh, 6.4 V
External power input	6-40 V
Charging	USB-C 5 V 2 A

COMMUNICATIONS AND DATA STORAGE

- 9PIN port: RS-232, PPS, Event
- USB OTG
- Internal LTE modem:
 - LoRa technology
 - Reliable link on up to 8 km baseline
 - Transmit power up to 100mW
 - Configurable 862-1020 MHz carrier
- Internal LTE modem
 - Global
 - Quad-band, 850/1900, 900/1800 MHz
- Built-in short-range Wi-Fi 802.11 b/g/n, WEP, WPA, WPA2 encryption
- Built-in short-range Bluetooth 4.0/2.1 EDR
- Data storage 16 GB internal memory
- Raw logs in RINEX, UBX
- External Radio Modem connectivity over RS-232/USB OTG
- RTCM 3.x input and output over Wi-Fi, Bluetooth, LoRa, USB, RS-232, NTRIP
- NMEA 0183, ERB output over Wi-Fi, Bluetooth, USB, RS-232
- ReachView 3 app for iOS and Android for configuration and surveying



What can we do with Reach RS2+?

Reach RS2+ provides centimeter-precision coordinates via of multiple wireless or wired channels, which makes it a universal tool for all kinds of applications that require precision, both for data capture and navigation.

With Reach RS2+ you can create your own survey project and manage the captured data. Assign names to each point taken. All the data can be exported as list of points, as a file DXF or ESRI Shapefile.

Reach RS2+ can provide accurate coordinates via Bluetooth/WiFi to your external device allowing the use of third-party software's (such as TCP-GPS, Carlson, Magnet Fields, etc).

Reach RS2+ allows to use the EMLID Caster network and connect via modem LTE to be used as the NTRIP base of other devices.

Reach RS2+ can store RINEX files and be used as equipment to perform PPK kinematic post-processing of drone flights.

Can communicate via Wi-Fi with third-party devices providing them with real-time RTK data.

ATyges
INGENIERÍA
www.atyges.es

ATyges - Distribuidor Oficial EMLID

Más info en: atyges.es/tienda/
95 20 20 600 - store@atyges.es
Av. Juan López Peñalver, 21
Parque Tecnológico de Andalucía, Málaga, España